


Needle Roller Bearings

With Inner Ring Inch Series



Designation	Dimensions				Basic Load Ratings	
	d	F	D	C	Dynamic	Static
					C_r N	C_{or} N
BRI61812	9.525	28.575	19.050	19.300	18090	20060
BRI82012	12.700	31.750	19.050	19.300	20430	24440
BRI82016	12.700	31.750	25.400	25.650	26970	33340
BRI102212	15.875	34.925	19.050	19.300	23440	27920
BRI102216	15.875	34.925	25.400	25.650	29550	37620
BRI122412	19.050	38.100	19.050	19.300	25950	37620
BRI122416	19.050	38.100	25.400	25.650	32710	44250
BRI142616	22.225	41.275	25.400	25.650	35400	50920
BRI142620	22.225	41.275	31.750	32.000	43660	66660
BRI162816	25.400	44.450	25.400	25.650	36520	54580
BRI162820	25.400	44.450	31.750	32.000	45040	71460
BRI183016	28.575	47.625	25.400	25.650	38970	61270
BRI183020	28.575	47.625	31.750	32.000	48060	80220
BRI203316	31.750	52.388	25.400	25.650	44770	68530
BRI203320	31.750	52.388	31.750	32.000	55230	89780
BRI223516	34.925	55.562	25.400	25.650	45780	72550
BRI223520	34.925	55.562	31.750	32.000	56490	95040
BRI243716	38.100	58.738	25.400	25.650	47560	78260
BRI243720	38.100	58.738	31.750	32.000	59470	104830
BRI243820	38.100	60.325	31.750	32.000	59470	104830
BRI243920	38.100	61.912	31.750	32.000	60120	107880
BRI264116	41.275	65.088	25.400	25.650	51820	91570
BRI264120	41.275	65.088	31.750	32.000	63940	119880