


Cylindrical Roller Bearings With Snap Ring Grooves

Full Complement, Sealed

Locating Bearings



Designation	Dimensions										Basic Load Ratings	
	d	D	B	C	C1	D1	m	r	t	X	Dynamic	Static
											C_r	C_{or}
					+0.2			min	min		N	N
SL045004-PP	20	42	30	29	24.7	40.2	1.8	0.3	0.5	22.5	41300	51450
SL045004-PP	20	42	30	29	24.7	40.2	1.8	0.3	0.5	22.5	41300	51450
SL045006-PP	30	55	34	33	28.2	53.0	2.1	0.3	0.5	25.5	51000	70350
SL045007-PP	35	62	36	35	30.2	60.0	2.1	0.3	0.5	27.5	64900	95000
SL045008-PP	40	68	38	37	32.2	65.8	2.7	0.6	0.8	28.5	78200	111200
SL045009-PP	45	75	40	39	34.2	72.8	2.7	0.6	0.8	30.5	94750	140400
SL045010-PP	50	80	40	39	34.2	77.8	2.7	0.6	0.8	30.5	102700	161500
SL045011-PP	55	90	46	45	40.2	87.4	3.2	0.6	1.0	36.0	120750	196000
SL045012-PP	60	95	46	45	40.2	92.4	3.2	0.6	1.0	36.0	142100	228800
SL045013-PP	65	100	46	45	40.2	97.4	3.2	0.6	1.0	36.0	143750	243600
SL045014-PP	70	110	54	53	48.2	107.1	4.2	0.6	1.0	42.0	193200	318000
SL045015-PP	75	115	54	53	48.2	112.1	4.2	0.6	1.0	42.0	228900	363000
SL045016-PP	80	125	60	59	54.2	122.1	4.2	0.6	1.5	48.0	229500	432000
SL045017-PP	85	130	60	59	54.2	127.1	4.2	0.6	1.5	48.0	253200	437500